



STRAIGHTWAY TAPER PLUG VALVES

CAST STEEL CLASS 900
VENTURI PATTERN
RECTANGULAR PORT

Class	Max. CWP	Test Pressure	Pattern	Connections	Port	Materials		Operation
						Body & Cover	Plug	
900	2220 Psi	Shell 3350 Psi Seat 2442 Psi	Straightway Venturi	Welding Ends ASME B 16.25 End to End ASME B 16.10	Rectangular	Cast Steel ASTM A 216 Grade WCB Cover: EN 10025 S355J0 S355J2G3	Cast Iron ASTM A 126 Class B	Manual
							Steel	

	WRENCH TYPE 8 L	GEAR TYPE C	GEAR TYPE D
Plug	DN 1 1/2" - 4"	DN 1 1/2" - 24"	DN 4" - 24"
Cast Iron	5-AT 70574 N	5-AT 70574 C	5-AT 70574 D
Steel	5-AT 70577 N	5-AT 70577 C	5-AT 70577 D

DN	A	B	C	D	E	F	H	I	L	M	N	O	P	S	T	X
1 1/2"	64	104	130	162	24	30	150	101	122	181	47			Inside pipe dimension to be specified by purchaser.	*50,3	*305
2"	64	115	145	177	24	30	150	101	137	181	47				*62,3	*368
2 1/2"	85	149	186	229	42	50	150	101	158	195	71				75	*419
3"	95	169	202	245	42	50	150	101	173	195	71				91	*381
4"	100	173	225	275	47	55	200	101	258	268	85				117	457
6"	114	211					200	101	302	268	85	46	424		172	610
8"	145	284					300	101	350	293	95	70	473		223	737
10"	157	290					300	101	435	361	135	69	569		278	838
12"	184	331					300	101	504	400	160	108	638		329	965
14"	192	353					300	101	510	400	160	108	644		362	*1029
16"	223	384					350	101	584	423	175	130	718		413	1130
18"	238	407					350	101	597	423	175	130	731		464	*1219
20"	273	471					350	101	638	460	176	168	772		516	1321
24"	310	535					350	101	760	483	196	192	894	619	*1549	

Note: * Not included in the standards.