




## TAPER PLUG VALVES

British standard pipe flanges for the petroleum industry and American standard pipe flanges



### CLASS 2500 CAST STEEL RAISED FACE FLANGES

Valve Size	R Flange Diameter	S Flange Thickness	T 1/4" Raised Face Diameter	U No. of Bolts	V Size of Bolts in	X Size of Holes	Y Bolt Circle Diameter
1/2"	133,4	30,2	34,9	4	3/4"	22,2	88,9
3/4"	139,7	31,8	42,9	4	3/4"	22,2	95,3
1"	158,8	34,9	50,8	4	7/8"	25,4	108,0
1 1/4"	184,2	38,1	63,5	4	1"	28,6	130,2
1 1/2"	203,2	44,5	73,0	4	1 1/8"	31,8	146,1
2"	235,0	50,8	92,1	8	1"	28,6	171,5
2 1/2"	266,7	57,2	104,8	8	1 1/8"	31,8	196,9
3"	304,8	66,7	127,0	8	1 1/4"	34,9	228,6
4"	355,6	76,2	157,2	8	1 1/2"	41,3	273,1
5"	419,1	92,1	185,7	8	1 3/4"	47,6	323,9
6"	482,6	108,0	215,9	8	2"	54,0	368,3
8"	552,5	127,0	269,9	12	2"	54,0	438,2
10"	673,1	165,1	323,9	12	2 1/2"	66,7	539,8
12"	762,0	184,2	381,0	12	2 3/4"	73,0	619,1